

UC200 系列



Lagermodell	Schachtdurchmesser		Größe (mm)									Grundlast	Grundlast	Gewicht
	In	(mm)	D	Bi	Sei	R	N	M	G	ds	T	Ruhig (kg)	Bewegen (kg)	(kg)
UCW201-8	1/2		40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.19
202-10	5/8		40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.18
203-11	11/16		40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.17
UCW201		12	40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.15
202		15	40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.2
203		17	40	26	15	1	10	16	4	10-32UHF M5X0.8	4	900	580	0.18
UC201-8	1/2		47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.2
202-10	5/8		47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.19
203-11	11/16		47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.18
204-12	3/4		47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.16
UC201		12	47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.21
202		15	47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.19
203		17	47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.18
204		20	47	31	17	I	12.7	18.3	4.5	1/4-28 M6X0.75	3.7	1000	630	0.16
UC205-14	7/8		52	34.1	17	1.5	14.3	19.8	5	1/4-28 M6X0.75	3.9	1100	710	0.22
205-15	15/16		52	34.1	17	1.5	14.3	19.8	5	1/4-28 M6X0.75	3.9	1100	710	0.2
205-16	1		52	34.1	17	1.5	14.3	19.8	5	1/4-28 M6X0.75	3.9	1100	710	0.19
UC205		25	52	34.1	17	1.5	14.3	19.8	5	1/4-28 M6X0.75	3.9	1100	710	0.19
UC206-17	1-1/16		62	38.1	19	1.5	15.9	22.2	5	1/4 28 M6X0.75	5	1540	1020	0.36
206-18	1-1/8		62	38.1	19	1.5	15.9	22.2	5	1/4 28 M6X0.75	5	1540	1020	0.34
206-19	1-3/16		62	38.1	19	1.5	15.9	22.2	5	1/4 28 M6X0.75	5	1540	1020	0.32

UC200 系列

206 20	1-1/4		62	38.1	19	1.5	15.9	22.2	5	1/4 28 M6X0.75	5	1540	1020	0.31
UC206		30	62	38.1	19	1.5	15.9	22.2	5	1/4 28 M6X0.75	5	1540	1020	0.31
UC207-20	1-1/4		72	42.9	20	2	17.5	25.4	6	5/16-24 M8X 1	5.7	2030	1400	0.52
207 21	1-5/16		72	42.9	20	2	17.5	25.4	6	5/16-24 M8X 1	5.7	2030	1400	0.5
207-22	1-3/8		72	42.9	20	2	17.5	25.4	6	5/16-24 M8X 1	5.7	2030	1400	0.48
20/-23	1-7/16		72	42.9	20	2	17.5	25.4	6	5/16-24 M8X 1	5.7	2030	1400	0.46
UC207		35	72	42.9	20	2	17.5	25.4	6	5/16-24 M8X 1	5.7	2030	1400	0.46
UC208 -24	1-1/2		80	49.2	21	2	19	30.2	8	5/16-24 M8X1	6.2	2300	1600	0.68
208-25	1-9/16		80	49.2	21	2	19	30.2	8	5/16-24 M8X1	6.2	2300	1600	0.64
UC208		40	80	49.2	21	2	19	30.2	8	5/16-24 M8X1	6.2	2300	1600	0.63
UC209-26	1-5/8	45	85	49. 2	22	2	19	30. 2	8	5/16-24 M8X1	6.4	2560	1810	0.78
209 27	1-11/16		85	49. 2	22	2	19	30. 2	8	5/16-24 M8X1	6.4	2560	1810	0.74
209-28	1-3/4		85	49. 2	22	2	19	30. 2	8	5/16-24 M8X1	6.4	2560	1810	0.7
UC209		45	85	49. 2	22	2	19	30. 2	8	5/16-24 M8X1	6.4	2560	1810	0.68
UC210-30	1-7/8		90	51.6	24	2	19	32.6	10	3/8-24 M10X 1.25	6.5	2750	2020	0.85
210-31	1-15/16		90	51.6	24	2	19	32.6	10	3/8-24 M10X 1.25	6.5	2750	2020	0.8
UC210		50	90	51.6	24	2	19	32.6	10	3/8-24 M10X 1.25	6.5	2750	2020	0.78
UC211-32	2		100	55.6	25	2.5	22.2	33.4	10	3/8-24 M10X1.25	7	3400	2550	1.22
211-34	2-1/8		100	55.6	25	2.5	22.2	33.4	10	3/8-24 M10X1.25	7	3400	2550	1.1
211-35	2-3/16		100	55.6	25	2.5	22.2	33.4	10	3/8-24 M10X1.25	7	3400	2550	1.05
UC211		55	100	55.6	25	2.5	22.2	33.4	10	3/8-24 M10X1.25	7	3400	2550	1.07
UC212-36	2-1/4	60	110	65.1	27	2. 5	25.4	39.7	10	3/8-24 M10X1.25	7.6	4100	3150	1.65
212-38	2-3/8		110	65.1	27	2. 5	25.4	39.7	10	3/8-24 M10X1.25	7.6	4100	3150	1.49
212-39	2-7/16		110	65.1	27	2. 5	25.4	39.7	10	3/8-24 M10X1.25	7.6	4100	3150	1.42
UC212		60	110	65.1	27	2. 5	25.4	39.7	10	3/8-24 M10X1.25	7.6	4100	3150	1.52

UC200 系列

UC213-40	2-1/2		120	65.1	28	2.5	254	39.7	10	3/8-24 M10X 1.25	8.9	4480	3470	1 88
UC213		65	120	65.1	28	2.5	254	39.7	10	3/8-24 M10X 1.25	8.9	4480	3470	1.8
UC214-44	2-3/4		125	74.6	30	2.5	30.2	44.4	12	7/16-20 M 1 2 X 1.5	89	4870	3810	2.07
UC214		70	125	74.6	30	2.5	30.2	44.4	12	7/16-20 M 1 2 X 1.5	89	4870	3810	2.06
UC215-47	2-15/16		130	77.8	32	2.5	33.3	44.5	12	7/16-20 M12 X 1.5	8.9	5200	4200	2.21
215-48	3		130	77.8	32	2.5	33.3	44.5	12	7/16-20 M12 X 1.5	8.9	5200	4200	2.11
UC215		75	130	77.8	32	2.5	33.3	44.5	12	7/16-20 M12 X 1.5	8.9	5200	4200	2.19
UC216-50	3-1/8		140	82.6	33	3	33.3	49.3	14	7/16-20 M 1 2 X 1.5	9.6	5700	4550	2.90
UC216		80	140	82.6	33	3	33.3	49.3	14	7/16-20 M 1 2 X 1.5	9.6	5700	4550	2.82
UC217-52	3-1/4		150	85.7	35	3	34.1	51.6	14	7/16-20 M1 2 X 1.5	10	6600	5320	3.56
UC217		85	150	85.7	35	3	34.1	51.6	14	7/16-20 M1 2 X 1.5	10	6600	5320	3.46
UC218-56	3-1/2		160	96	37	3	39.7	56.3	15	7/16-20 M 1 2 X 1.5	11	7550	6170	4 62
UC218		90	160	96	37	3	39.7	56.3	15	7/16-20 M 1 2 X 1.5	11	7550	6170	4.53