




SD600 系列



Lagersitzmodell	Schachtdurchmesser	Abmessungen (mm/in)																	轴承座重量	Lagermodell	Anspannungssatz	Positionierungskreis	
		D	A	B	C	G	H	L	W	M	N	S	u	v	d2	d3	fi	K				Modell	Menge
SD634	150	360	740	270	65	130	210	300	420	610	170	M30	36	55	153	183	10	13.8	140	22334K	H2334	SR360x10	1
SD636	160	380	780	290	70	136	225	320	450	640	180	M36	43	62	163	193	10	13.8	170	22336K	H2336	SR380x10	1
SD638	170	400	820	300	70	142	240	330	475	680	190	M36	43	62	173	203	10	13.8	200	22338K	H2338	SR400X10	1
SD640	180	420	860	320	85	148	250	350	500	710	200	M36	43	62	183	213	10	13.8	230	22340K	H2340	SR420x10	1
SD644	200	460	920	330	85	155	280	360	550	770	210	M36	43	62	203	240	11	15.7	290	22344K	H2344	SR460x10	1
SD648	220	500	990	370	100	165	300	390	590	830	230	M42	50	70	223	260	11	15.7	350	22348K	H2348	SR500X10	1
SD652	240	540	1060	390	100	175	325	410	640	890	250	M42	50	70	243	286	12	17.4	450	22352K	H2352	SR540x10	1
SD656	260	580	1110	420	110	185	355	440	690	930	270	M48	58	77	263	306	12	17.4	550	22356K	H2356	SR580x10	1