


SNL3100 系列



Lagersitzmodell	Schachtdurchmesser	Abmessungen (mm/in)														轴承座重量	Lagermodell	Anspannungssatz	Positionierungskreis	
		D	A	B	C	G	H	L	W	M	N	u	v	J	S				Modell	Menge
SNL3134	150	280	510	180	70	108	170	230	333	430	100	28	34	14	M24	70	23134K	H3134	SR280X10	2
SNL3136	160	300	530	190	75	116	180	240	353	450	110	28	34	15	M24	79	23136K	H3136	SR300X10	2
SNL3138	170	320	560	210	80	124	190	260	375	480	120	28	34	10	M24	100	23138K	H3138	SR320X10	2
SNL3140	180	340	610	230	85	132	210	280	411	510	130	35	42	10	M30	130	23140K	H3140	SR340X10	2
SNL3144	200	370	640	240	90	140	220	290	434	540	140	35	42	12	M30	146	23144K	H3144	SR370X10	2
SNL3148	220	400	700	260	95	148	240	310	474	600	150	35	42	12	M30	190	23148K	H3148	SR400X10	2
SNL3152	240	440	770	260	100	164	260	320	516	650	160	42	50	13	M36	230	23152K	H3152	SR440X10	2
SNL3156	260	460	790	280	105	166	200	320	551	670	160	42	50	16	M36	260	23156K	H3156	SR460x10	2
SNL3160	280	500	830	310	110	180	300	350	591	710	190	42	50	22	FVB6	320	23160K	H3160	SR500x10	2
SNL3164	300	540	880	330	115	196	320	370	631	750	200	42	50	23	M36	350	23164K	H3164	SR540X10	2
SNL3168	320	590	950	360	120	210	340	400	675	810	220	42	50	24	M30	427	23168K	H3168	SR580x10	2
SNL3172	340	600	1000	360	120	212	350	400	695	840	220	42	50	30	M36	458	23172K	H3172	SR600X10	2
SNL3176	360	620	1040	360	120	214	360	400	715	870	220	42	50	30	M36	470	23176K	H3176	SR620x10	2
SNL3180	380	650	1120	390	125	220	380	430	755	950	240	46	60	30	M36	595	23180K	H3180	SR650X10	2
SNL3184	400	700	1170	420	130	244	410	460	810	1000	260	48	60	35	M42	709	23184K	H3184	SR700X10	2
SNL318S	410	720	1220	430	135	246	420	460	835	1030	260	48	60	35	M42	751	23188K	H3188	SR720X10	2
SNL3192	430	760	1280	440	145	260	440	470	880	1070	260	45	60	35	M42	859	23192K	H3192	SR760X10	2
SNL3196	450	790	1330	440	155	26a	460	470	920	1110	260	56	70	35	M4B	947	23196K	H3196	SR790x10	2