



SN3100 系列



Lagersitzmodell	Wellendurchmesser mm	Größe (mm)																		Lagergewicht (kg)	Lagermodell	Anspannungssatz	Positionierungskreis	
		D	A	B	C	G	H	L	W	M	S	S	N	u	V	d ₂	d ₃	f ₁	f ₂				Modell	Menge
(S)SN3122	100	180	380	110	40	66	112	160	218	320	M24	M16	60	26	32	102	125	8	10.8	17	23122K	H3122	SR180x10	1
(S)SN3124	110	200	410	120	45	72	125	175	240	350	M24	M16	70	26	32	113	135	8	10.7	20	23124K	H3124	SR200x10	1
(S)SN3126	115	210	410	120	45	74	140	185	270	350	M24	M16	70	26	32	118	140	8	10.7	25	23126K	H3126	SR210x10	1
(S)SN3128	125	225	445	130	50	78	150	175	285	380	M24	M20	70	28	36	128	154	9	12.2	30	23128K	H3128	SR225x10	1
(S)SN3130	135	250	500	150	50	90	150	205	305	420	M30	M24	80	33	42	138	164	9	12.2	38	23130K	H3130	SR250x10	1
(S)SN3132	140	270	530	160	60	96	160	220	325	450	M30	M24	90	33	42	143	173	10	13.7	46	23132K	H3132	SR270x10	1