



SAF517-544 系列



Lagersitzmodell	Wellendurchmesser mm	Größe (mm)													Lagergewicht (kg)	Lagermodell	Anspannungssatz	Positionierungskreis	
		D	A	B	C	G	H	L	W	N	e _{max}	e _{min}	s ₂	s ₄				Modell	Menge
SAF517	2-15/16	150	330	89	32	46	95.3	122	186	54.1	279	251	M20	M16	12.3	1217K	HA217	SR150x9	2
SAF517	2-15/16	150	330	89	32	46	95.3	122	186	54.1	279	251	M20	M16	12.3	2217K 22217K	HA317	SR150x10	1
SAF518	3-3/16	160	349	99	33	50	101.6	140	197	54.1	295	264	M20	M16	15.4	1218K	HA218	SR160x10	2
SAF518	3-3/16	160	349	99	33	50	101.6	140	197	54.1	295	264	M20	M16	15.4	2218K 22218K	HA318	SR160x10	1
SAF520	3-7/16	180	387	111	45	58	114.3	148	222	60.5	333	295	M24	M20	27.3	1220K	HA220	SR180x11	2
SAF520	3-7/16	180	387	111	45	58	114.3	148	222	60.5	333	295	M24	M20	27.3	2220K 22220K	HA320	SR180x10	1
SAF522	3-15/16	200	419	121	51	63	125.4	164	245	69.9	368	321		M20	35	1217K	HA222	SR150x12.5	2
SAF522	3-15/16	200	419	121	51	63	125.4	164	245	69.9	368	321		M20	35	2222K 22222K	HA322	SR150x10	1
SAF524	4-3/16	215	419	121	54	68	133.4	181	260	69.9	368	337		M20	43.2	22224K	HA3124	SR215x10	1
SAF526	4-7/16	230	467	130	61	74	152.4	197	292	82.6	406	372		M24	58.6	22226K	HA3126	SR230x10	1
SAF528	4-15/16	250	511	149	61	78	152.4	187	298	85.9	435	406		M24	62	22228K	HA3128	SR250x10	1
SAF530	5-3/16	280	540	159	64	83	160.4	207	318	95.3	464	432		M24	76.8	22230K	HA3130	SR270x10	1
SAF532	5-7/16	290	559	159	67	90	169.9	216	338	95.3	489	442		M24	81.3	22232K	HA3132	SR290x10	1
SAF534	5-15/16	310	629	172	70	96	179.4	235	360	108	549	492		M24	104.5	22234K	HA3134	SR310x10	1
SAF536	6-7/16	320	680	181	76	96	190.5	245	378	117.6	600	530		M24	117.6	22236K	HA3136	SR320x10	1
SAF538	6-15/16	340	711	191	80	102	200	267	398	114.3	619	549		M30	135	22238K	HA3138	SR340x10	1
SAF540	7-3/16	360	749	203	86	108	209.6	279	419	127	635	572		M30	167.5	22240K	HA3140	SR360x10	1
SAF544	7-15/16	400	832	222	95	118	241.3	298	473	133.4	708	629		M30	230.2	22244K	HA3144	SR400x10	1